



HEW-12500 (24V) BA2624

80 ft. (26 m.) of 3/8" (9.5 mm.) galvanized aircraft cable with replaceable clevis hook

P/N: 7346113 = BA2624

FEATURES & SPECIFICATIONS

Rated Line Pull :	12500 lbs. (5665 kg.) Single-line
Motor:	6.6 hp/24V, Series Wound Motor
Control:	Remote switch, 12' (3.7 m.) lead
Gear Train:	3-Stage Planetary
Gear Ratio:	193,6
Clutch :	Sliding Ring Gear
Brake:	Automatic In-The-Drum
Drum size:	Dia. 2.5" (63.5 mm.). Length 8.75" (222 mm.)
Wire Rope:	80' 3/8" dia. (26 m., 9.5 mm. dia.)
Fairlead:	4-way roller fairlead
Remote Control:	Included
Recommended Battery:	650 CCA minimum for winching
Battery Leads:	25 mm ² , 72" (1.83 m.)
Finish:	Black
Weight:	83 lbs. (38 kg.)
Overall dimensions:	(L×W×H) 21.3 × 6.3 × 8.6 inch (542 × 160 × 218 mm.)
Mounting Bolt Pattern:	10.00 ± 0.015 IN × 4.50 ± 0.010 IN (254.0 × 114.3 mm.)

Line Speed & Amp Draw-First Layer

Line Pull	lbs.	0	2000	4000	6000	8000	10000	12000	12500	
	kgs	Lade	907	1814	2722	3629	4532	5440	5665	
Line Speed	fpm	24V	23,616	15,42	12,46	10,5	9,184	8,528	7,708	7,216
	mpm	24V	7,2	4,7	3,8	3,2	2,8	2,6	2,4	2,2
Motor	amps		38	62	85	108	131	155	178	183

Line Pull & Cable Capacity

Layer of Cable		1	2	3	4
Rated Line Pull per Layer	lbs.	12500	10700	9575	8800
	kgs	5665	4850	4340	3790
Cable capacity per Layer	ft	16	42	72	80
	mpm	5	12	21	26

